

GROUT PAINT



DUNLOP GROUT PAINT is the ideal way to revive a tiled area without removing old or discoloured grout. Suitable over most grout joints, DUNLOP GROUT PAINT can be used both indoors on walls and floors* and outdoors on walls. *Grout Paint may wear faster in areas subject to regular traffic (floors) or frequent exposure to water and chemicals (showers).

JOINT PREPARATION

Scrub the grout joints to be painted with DUNLOP TILE & GROUT CLEANER and allow the joints to dry thoroughly before applying DUNLOP GROUT PAINT.

APPLICATION

1. Shake bottle vigorously for 30 seconds whilst squeezing the bottle intermittently.
2. Remove the clear overcap then twist the open/close brush applicator to open in a counter-clockwise rotation.
3. Holding the bottle upside down, gently squeeze the bottle to allow the grout paint to flow into the brush applicator.
4. Brush the paint into the grout joint, ensuring that excess paint is not left on the surface of the joint. Try and avoid getting grout paint on the face of the tile.
5. Allow grout paint to set for 15-20 min. Once touch dry, the grout paint can be cleaned off the tile. Spray a fine mist of water over the project area and let stand for 3-5min. Using a sponge or cloth, lightly scrub the excess grout off the face of the tiles and lightly clean the whole project area.
6. Ensure brush is cleaned in water after use.
7. Allow to cure for 2 hours and then polish the project area with a soft cloth.
8. When using on outdoor walls, protect the painted area from rainfall for 24 hours after application.

DRYING TIME

Grout Paint will be set after 24 hours, after which showers can be exposed to water. Allow longer for lower temperatures or high humidity.

COVERAGE

The following coverage per 250ml will vary depending on joint width & application.

Tile Size (LxW)	1.5mm	3mm	5mm	10mm
25x25	9m ²	5m ²	3m ²	1m ²
100x100	36m ²	8m ²	11m ²	5m ²
330x330	120m ²	60m ²	36m ²	18m ²
600x600	200m ²	100m ²	65m ²	35m ²

CAUTION

Do not use in expansion or movement joints. Not suitable for use in swimming pools or for external floors. The long term integrity of the grout paint will be compromised in showers due to frequent exposure to water, soaps, chemicals. **For tiles that have a textured or porous surface, check ease of cleaning in an inconspicuous area before use. Not suitable for use over epoxy grout.**

SHELF LIFE

12 months in original unopened packaging.

CLEAN UP

Clean brush immediately after use with warm water so that it can be reused for multiple applications, replace the clear overcap.

SAFETY

Wear gloves when working. If the product enters the eyes, wash with clean water for at least 15 minutes and seek medical advice. If swallowed do not induce vomiting, give a glass of water and contact a doctor. MSDS available on the Dunlop website at www.dunlopdij.com

ARDEX AUSTRALIA PTY LTD.

ABN 82 000 550 005

7/20 Powers Rd, Seven Hills NSW 2147

1300 788 780

ARDEX NEW ZEALAND LTD

32 Lane Street Woolston, Christchurch NZ

Ph +64 3 373 6900

USER NOTES

The technical details and recommendations contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of publication. It is the responsibility of the user to ensure that the products are used in accordance with DUNLOP product instructions and in applications for which they are intended.